9.0 FENSTRATION PRODUCT RATING CERTIFICATE (IP)

U-factor: (Btu/h·ft²·°F) Certificate Authorization SHGC: VT: Name: Company: Signature: Date: STIPULATES THAT THE MATERIALS LISTED ON THIS CERTIFICATE WERE INSTALLED ON THE PROJECT IDENTIFIED BELOW PROJECT INFORMATION: Street Address: City: State: GLAZING CONTRACTOR / INSTALLER: Contact Person: Street Address: Phone Number: City: State: GLAZING MATERIAL SUPPLIER: Contact Person: **FABLE 1 - GLAZING** Street Address: Phone Number: City: State: Zip: Glass and Spacer Type: Center-of-glass (C.O.G.) U-factor: Center-of-glass (C.O.G.) SHGC: Center-of-glass (C.O.G.) VT: Btu/h·ft2.°F FRAMING MATERIAL SUPPLIER: Contact Person: YKK AP America Inc David Warden Phone Number: Street Address: 101 Marietta Street NW, Suite 2700 678-838-6000 City: State: Zip 30303 Atlanta Georgia **U-factor Matrix** SHGC Matrix VT Matrix Btu/h·ft2.°F Product Line: C.O.G. Overall C.O.G. Overall C.O.G. Overall YCW 750 OGP Curtain Wall U-factor U-factor SHGC SHGC VT VT Curtain Wall 0.48 0.53 0.75 0.68 0.75 0.67 0.70 0.46 0.52 0.64 0.70 0.63 The overall ratings for U-factor, SHGC and VT are 0.44 0.50 0.65 0.59 0.65 0.58 based on a size of 78.750 in. X 78.750 in. as required in NFRC 100 and NFRC 200. 0.42 0.48 0.60 0.55 0.60 0.54 0.55 0.50 0.55 0.49 0.47 0.40 0.45 0.50 0.46 0.50 0.45 Overall U-factors, Solar Heat Gain Coefficients (SHGC) and 0.38 0.45 0.40 0.41 0.45 0.36 0.43 Visible Transmittances (VT) listed in the matrix were 0.40 0.37 0.40 0.36 0.34 0.42 determined in accordance with NFRC 100 and NFRC 200 0.32 0.40 0.35 0.32 0.35 0.31 respectively by an accredited, independent laboratory. 0.27 0.30 0.38 0.30 0.28 0.30 ACCREDITED INDEPENDENT LABORATORY: 0.25 0.23 0.25 0.22 **Architectural Testing** 0.28 0.37 0.20 0.18 0.26 0.35 0.20 0.19 Reference NFRC 100 Report #: D1120.02-116-45 0.15 0.13 0.24 0.33 0.15 0.14 Reference 507-12 Report #: D1120.01-116-45 0.10 0.10 0.10 0.09 Reference AWS Test Report #: C9520.01-550-47 0.22 0.32 0.05 0.05 0.04 0.05 0.20 0.30 0.18 0.28 Air Leakage less than or equal to 0.06 cfm/ft² Directions: Fill out form completely. Determine the Overall Rating for this project by using the C.O.G. U-factor (winter-time), at a test pressure of 6.24 PSF when tested in 0.16 0.26 accordance with (check one) C.O.G. SHGC, C.O.G. VT from Table 1 and looking up the 0.24 0.14 AAMA/WDMA/CSA 101/I.S.2/A440 overall rating from Table 2. Indicate the Overall Rating in the space above. Linear interpolation is permitted. 0.12 0.23 Х ASTM E283 (6.24 PSF) 0.10 0.21 NFRC 400

OVERALL RATING