## 9.0 FENSTRATION PRODUCT RATING CERTIFICATE (IP)

	,						OVERALL RATING		
Certificate Authorization						U-factor: (Btu/h·ft²·°F)			
						SHGC:			
						VT:	-		
Name:						Company:			
Signature: Date:									
STIPULATES THAT THE MATERIALS LISTED ON THIS CERTIFICATE WERE INSTALLED ON THE PROJECT IDENTIFIED BELOW									
PROJECT INFORMATION:									
	Street Address:								
	City:						State: Zip:	.	
	GLAZING CONTRACTOR / INSTALLER:						Contact Person:	.	
	Street Address:						-	.	
	Street Address:						Phone Number:		
	City:					State: Zip:			
	GLAZING MATERIAL SUPPLIER:					Contact Person:			
TABLE 1 - GLAZING	Street Address:					Phone Number:			
	Olioti Audioss.						Tione Named.		
	City:						State: Zip:	•	
							#	.	
	Glass and Spacer Type:								
ΔT	Center-of-glass (C.O.G.) U-factor:					Center-of-glass (C.O.G.) SHGC: Center-of-glass (C.O.G.) VT:			
	Btu/h·ft²-°F								
	FRAMING MATERIAL SUPPLIER:					Contact Person:			
	YKK AP America Inc Street Address:						David Warden Phone Number:	.	
	101 Marietta Street NW, Suite 2700						678-838-6000		
TABLE 2 - FRAMING	City:						State: Zip:	.	
	Atlanta					Georgia 30303	.		
	U-factor Matrix Btu/h·ft <sup>2</sup> ·°F		SHGC Matrix		VT Matrix				
	C.O.G.		0.0.0	Overell	C.O.G.	Overell	Product Line: YCW 750 XTP		
	U-factor	Overall U-factor	C.O.G. SHGC	Overall SHGC	VT	Overall VT	Curtain Wall		
	0.48	0.52	0.75	0.68	0.75	0.67			
	0.46	0.50	0.70	0.64	0.70	0.63	The overall ratings for U-factor, SHGC and VT are		
	0.44	0.49	0.65	0.59	0.65	0.58	based on a size of 78.750 in. X 78.750 in. as		
	0.42	0.47 0.46	0.60 0.55	0.55 0.50	0.60	0.54 0.49	required in NFRC 100 and NFRC 200.		
	0.40	0.44	0.50	0.46	0.50	0.45	Overall U-factors, Solar Heat Gain Coefficients (SHGC) a	and	
	0.36	0.42	0.45	0.41	0.45	0.40	Visible Transmittances (VT) listed in the matrix were		
	0.34	0.41	0.40	0.37	0.40	0.36	determined in accordance with NFRC 100 and NFRC 2		
	0.32	0.39	0.35	0.32	0.35	0.31	respectively by an accredited, independent laboratory	<u>'.                                    </u>	
	0.30 0.28	0.38	0.30 0.25	0.28 0.23	0.30	0.27 0.22	ACCREDITED INDEPENDENT LABORATORY:  Architectural Testing Inc.		
	0.26	0.34	0.20	0.19	0.20	0.22	Reference NFRC 100 Report #: E2605.02-116-45	-	
	0.24	0.33	0.15	0.14	0.15	0.13	Reference 507-12 Report #: E2605.01-116-45		
	0.22	0.31	0.10	0.10	0.10	0.09	Reference AWS Test Report #: K0477.01-550-44-R	1	
	0.20	0.30	0.05	0.05	0.05	0.04			
	0.18	0.26	Air Leakage less than or equal to 0.06 cfm/ft <sup>2</sup> at a test pressure of 6.24 PSF when tested in				Directions: Fill out form completely. Determine the Overall Rating for this project by using the C.O.G. U-factor (winter-time), C.O.G. SHGC, C.O.G. VT from Table 1 and looking up the overall rating from Table 2. Indicate the Overall Rating in the space above. Linear interpolation is permitted.		
	0.16	0.25	accordance with (check one)						
	0.14 0.12	0.23 0.21	AAMA/WDMA/CSA 101/I.S.2/A440  X ASTM E283 (6.24 PSF)						
	0.12	0.19		NFRC 400	,				