




Step	N/A	Done	Instruction ⁽¹⁾	*Ref
1.	<input type="checkbox"/>		5/16" diameter weep holes should be drilled in the sill glass pocket. Weep holes should be located at ¼ points of each daylight opening between vertical mullions.	pg.5
2.	<input type="checkbox"/>		Vertical mullions and jambs must be notched to fit with continuous head. See Detail 9 and Detail 10 .	pg.7
3.	<input type="checkbox"/>		Interior glass stops should be cut to length of daylight opening minus 1/32".	pg.8
4.	<input type="checkbox"/>		Exterior glass stops should be cut to a length of daylight opening Minus 1/32"	pg.9
5.	<input type="checkbox"/>		End dams must be installed and sealed at the ends of the continuous head and sill members. See Detail 16 .	pg.10
6.	<input type="checkbox"/>		Prior to attachment of vertical mullions to the head and sill members, apply sealant to the profile of the vertical members. See Detail 18 .	pg.12
7.	<input type="checkbox"/>		Prior to attachment of intermediate horizontal members to vertical members, apply sealant to the profile of the horizontal members. See Detail 18 .	pg.12
8.	<input type="checkbox"/>		Frames should be installed level, square, and true in the building openings with a minimum 3/8" caulk joint around the entire perimeter of the frames. Shims are required at all perimeter anchor locations. Seal over heads of all perimeter anchors.	pg.15
9.	<input type="checkbox"/>		Water deflectors are required at the ends of all intermediate horizontals. Attach water deflectors with pre-applied tape and seal perimeter of water deflector. Seal ramp of the deflector to the glazing reglet walls See Detail 29 .	pg.19 
10.	<input type="checkbox"/>		Interior and exterior perimeter seals are required. See Detail 31 .	pg.20
11.	<input type="checkbox"/>		Seal all vertical to horizontal joints. See Detail 32 .	pg.20
12.	<input type="checkbox"/>		Vertical gaskets should be cut to a length of daylight opening plus ¼" per foot of daylight opening. Horizontal gaskets should be cut to a length of daylight opening plus ¼" per foot of daylight opening. Horizontal/vertical gasket corners should be sealed. Detail 33 .	pg.21 
13.	<input type="checkbox"/>		Apply sealant to the profile of the interior glass stops prior to installation. Detail 38 .	pg.24

 Denotes short video clips for this step are available for viewing at www.ykkap.com/productmaster

(1) Please review the entire installation manual prior to fabrication and installation. This checklist is provided as a quick review during and after installation. Visit www.ykkap.com/productmaster.

Project Name: _____