YSD 700

Heavy Duty Architectural Sliding Balcony Door



BALCONY DOORS

Heavy Commercial Quality

The YSD 700 is a heavy duty sliding door designed to comply with higher structural loads while maintaining an aesthetic appearance. The sliding doors are fully manufactured by YKK AP and shipped knocked-down for field assembly to reduce shipping cost. Operable and sidelite panels are factory glazed for easy installation. Standard heavy duty hardware rollers are supplied to provide years of worry-free operation.

Product Options & Features

- Available configs: OX, XO, OXO, & OXXO
- AAMA/WDMA 101/I.S. 2-97/NAFS-02
 - HC-120 Grade
- Accepts monolithic or insulating glass
- Factory glazing (active panels) and Screens
- Standard heavy-duty hardware, including stainless steel tandem rollers & track cover allow for unimpaired operation








SYSTEM SPECIFICATIONS


YSD 700


System Depth	Glass	Air Infiltration	Water Infiltration	Thermal Performance	Acoustical Performance	Forced Entry Resistance
7"	1" IGU with Low-E (C.O.G. U-factor: 0.29)	Sliding Doors: 0.30 CFM/FT ² @ 6.24 PSF (299 Pa)	Static: 15 psf (718 Pa) Dynamic: 20 psf (958 Pa)	U-factor: 0.61 BTU/HR●FT ² ●°F* CRF: Minimum of 21 on frame**	Std STC: 30 Std OITC: 26	Tested in accordance and meets the requirements of Performance Grade 10
					Lam STC: 30 Lam OITC: 27	
Testing Standards		ASTM E 283	ASTM E 331 & 547	*NFRC 100 & **AAMA 1503	ASTM E 90 & 1425	ASTM F 842 & TAS 202
Structural Performance		HC Performance Grade 120				
Available Finishes		Factory Anodized (AAMA 612) and Organic Paints (AAMA 2604 & AAMA 2605)				


Note: Balcony Door configuration will affect specifications.

CONFIGURATIONS











Additional information including CAD details, CSI specifications, Test Reports and Installation instructions are available online at: www.ykkap.com/commercial/product/sliding-doors/ysd-700/