





Our ProTek® single 35H/50H entrance doors with nonemergency egress, employ a three point locking system to ensure they remain secured during the strong cyclical winds associated with hurricanes. The three point locking system features a single actuation system for ease of use, keyed exterior cylinder, and interior thumbturn.

Description

P-2242:

Header

Bo₁t

- Adams Rite® series Hookbolt Lock, Header and Threshold Bolts. Standard backset is 1-1/2" (medium & wide stile doors).
- Assembly accepts any standard 1-5/32" diameter mortised cylinder, thumbturn cylinder, or dummy cylinder. All operating cylinder types require MS cam.
- Considered maximum security for YKK AP standard and upgraded locking devices.

Compatible Entrances

35D/50D, 40M/50M & 35H/50H

YKK AP Part Numbers

P-2101: Hook Lock (1-1/2" backseat)

P-2242: Header Bolt H-3211: Threshold Bolt

Material Composition

Aluminum, Stainless Steel and Mill Finish

Dimensions

Case: 1" x 6" x backset depth

Bolt: $5/8" \times 1-3/8"$ with 13/16" throw

Faceplate: $1" \times 6-7/8"$

Hardware Vendor



ASSA ABLOY

Vendor Part or Series

Adams Rite® MS-1850 (Hook Lock 1-1/2" backset)

Adams Rite® 4016 (Header Bolt) Adams Rite® 4015 (Threshold Bolt)

21-5034-00

P-2101 / P-2242 / H-3211