





Our ProTek® pair 35H/50H entrance doors with a nonemergency egress, employ a five point locking system to ensure that they remain secured during the strong cyclical winds associated with hurricanes. The active leaf employs a three-point locking system that features a single actuation system for ease of use, keyed exterior cylinder and thumbturn. The inactive leaf utilizes a two point locking system that is activated by an interior thumbturn.

# **Description**

P-2151:

Flush

Bo<sub>1</sub>t

- Adams Rite® series Hookbolt Lock, Header, Threshold and Flushbolts. Standard backset is 1-1/2" (medium & wide stile doors).
- Assembly accepts any standard 1-5/32" diameter mortised cylinder, thumbturn cylinder, or dummy cylinder. All operating cylinder types require MS cam.
- Considered maximum security for YKK AP standard and upgraded locking devices.

# **Compatible Entrances**

35D/50D. 40M/50M & 35H/50H

#### **YKK AP Part Numbers**

**P-2101:** Hook Lock (1-1/2" backseat)

P-2242: Header Bolt H-3211: Threshold Bolt P-2151: Flushbolt

## **Material Composition**

Aluminum, Stainless Steel and Mill Finish

#### Hardware Vendor



# **ASSA ABLOY**

## **Vendor Part or Series**

Adams Rite® MS-1850 (Hook Lock 1-1/2" backset)

Adams Rite® 4016 (Header Bolt) Adams Rite® 4015 (Threshold Bolt) Adams Rite® MS-1880 (Flushbolt)

21-5035-00

# P-2101 / P-2242 / H-3211 / P-2151