



Commercial
Standard Entrance
Hardware



Description

- Adams-Rite® 7100 Series Electric Strike
- Remote electrical control of any door with Adams Rite® 4510 Deadlatch (H-3205/3206/3207/3708)
- Draw is 0.17amps at 24 VAC
- Electrical Actuation unlocks the keeper, releasing the Deadlatch bolt
- Modular packaged with Faceplate (Clear or Black)

Compatible Entrances

20D/35D/50D, 25T/35T/50T, 40M/50M,
& 35H/50H (blast only)

Material Composition

Stainless Steel

Finishes

Faceplate Finish: 628 Clear or 335 Black

Dimensions

Case: 1" x 3-3/8" x 1-5/8" deep

Strike Opening: 5/8" x 1-7/16" x 1/2" deep

Bolt: 5/8" x 1-3/8" with 13/16" throw

Faceplate: 1-1/4" x 4-7/8"

Hardware Vendor



ASSA ABLOY

Vendor Part or Series

Adams Rite® MS-7100-540-628-00 (Flat Shape/Single Door/Clear)
Adams Rite® MS-7100-540-335-00 (Flat Shape/Single Door/Black)
Adams Rite® MS-7101-540-628-00 (Radius Shape/Pair or Inactive/Clear)
Adams Rite® MS-7101-540-335-00 (Radius Shape/Pair or Inactive/Black)

21-5037-01

H-3504 / H-3505

Optional Electric Strike for Deadlatches