

# P-52497

## Standard Concealed Vertical Rod Panic Exit Device



### Hardware Description

- Concealed Panic Device has concealed vertical lock rods and top latch mechanism in door stile.
- Depressing touchpad retracts the bottom rod from threshold and releases top latch from transom bar/header mounted barrel strike.
- Upon closing, top latch re-engages strike securely and frees bottom bolt to engage threshold. Door is then locked from exterior.
- Panic device can be deactivated or “dogged” with optional cylinder key or allen key in active housing.
- Housings are cast aluminum with extruded aluminum touchpad. Rim cylinder diameter of 1-5/32” (29.4mm); cylinder specified above.

### Vendor of Hardware

First Choice Building Products

### Vendor Part Number

3600 Series - 369036

### Application

- Concealed vertical rod device eliminates removable mullion obstruction on pairs of doors.
- Device when activated locks entrance on exterior and permits egress from building without the use of key.
- Touchpad design offers increased building security and reduces the risk of code infringements.

### Material Composition

Anodized Aluminum Push Bar and Channel  
Die Cast Aluminum End Caps  
Stainless Steel Strikes  
Steel Latch Bolts  
3/8” Steel Vertical Rods

### Finishes

628 Clear, 335 Black or Factory Special Order

### Usage

For use on 20D/35D/50D, 40M/50M, 25T/35T/50T, 35XT/50XT, and 35H/50H