YOW 225

Operable Window with Monolithic or Insulating Glass



A Quality Window at a Great Value

The YOW 225 windows have been designed and engineered to provide a quality window that will be worry free. The windows may be glazed with either monolithic or insulating unitsand has been developed to provide a variety of configurations to accommodate project requirements. The vents are flush with the frame thus eliminating unsightly overlap. The windows may be installed as independent units or configured to fit most YKK AP storefronts, window wall, or curtain wall systems.

Product Options & Features

- AAMA/WDMA/I.S. 2-97
 - AW-65 (Operable), AW-100 (Fixed)
- Available configs: Casement Outswing/Inswing, Project Out and In, Fixed
- Standard Heavy Duty Hardware
- Factory glazing and screens available
- Head/Jamb Receptors and Stacking Mullions
- Accepts 1/4" or 1" insulated glass








YOW 225

SYSTEM SPECIFICATIONS						
Base Depth	Glazing & Config	Glass	Air Infiltration	Water Infiltration	Thermal Performance	Acoustical Performance
2-1/4"	Laminated & Casement Out/In, Project Out/In or Fixed	1" IGU with Low-E (C.O.G. U-factor: 0.29)	0.10 CFM/FT ² (1.83 m ³ /h·m ²) @ 6.24 PSF (299 Pa)	Static Operable: 12 PSF (575 Pa) Static Fixed: 15 PSF (718 Pa)	Operable U-factor: 0.51 BTU/HR•FT2•°F* Fixed: 0.49 BTU/HR•FT2•°F* Operable CRF: Minimum of 55** Fixed: Minimum of 57**	Operable STC: 33 Operable OITC: 26
2-1/4						Fixed STC: 36 Fixed OITC: 27
Testing Standards			ASTM E 283	ASTM E 331 & AAMA 501	* NFRC 102 & ** AAMA 1503	ASTM E 90 & 1332
Product Testing			AW-65 Operable, AW-100 Fixed, AAMA/WDMA/I.S.2-97			
Available Finishes			Factory Anodized (AAMA 612) and Organic Paints (AAMA 2605)			



Additional information including CAD details, CSI specifications, Test Reports and Installation instructions are available online at: www.ykkap.com/commercial/product/architectural-windows/yow-225/