

YHC 300 SSG CASSETTE SPECS				
Base Depth	7-11/16"			
Sightline	3"			
Config	Structural Silicone Glazed / Front Set			
Tested Glass	1-5/16" Laminated IGU with Low-E (C.O.G. U-Factor: 0.29)			
Test	Results	Standards		
Air Infiltration	0.06 CFM/FT ² (1.10 m ³ /h·m ²) @ 6.24 PSF (299 Pa)	ASTM E 283		
Water Infiltration	Static: 15 PSF (718 Pa) Dynamic: 15 PSF (718 Pa)	ASTM E 331 AAMA 501		
Acoustical	Laminated STC: 39	ASTM E 90		


Thermal Performance								
Mullion Depth	U-Factor - BTU/hr-ft².°F				CRF			
3" x 7-11/16"	0.38	0.37	0.35	0.33	0.31	0.30	81	68
Center of Glass	0.30	0.28	0.26	0.24	0.22	0.20	Frame	Glass
AAMA 507				AAMA	A 1503			

Finish Options				
Туре	Standard			
Organic Paints	AAMA 2605			


Product Approvals					
Missile Level A, D, E	Wind Zone 3				
Hurricane HVHZ	International ICC				
Florida FBC	Texas TDI				

Mullion Depth Options
Low (45-55 PSF)
5-21/32"
Med (60-90 PSF)
7-11/16"
High (90-130 PSF)
10-1/2"

Standard vs Spliced Mullions




Standard horizontal mullion for typical single-span applications



Horizontal splice joint to accommodate multi-span applications

Cassette Glazing - A Closer Look



WARMER INTERIOR SURFACES

Greater occupant comfort and increased resistance to condensation

SPECIALLY DESIGNED FITTING

Specially created mullion to help secure and interlock pre-glazed window unit

CASSETTE PANELS

Glass is structurally silicone glazed to an aluminum carrier frame (cassette) in a clean, controlled shop environment. The glazed cassettes are then inserted, rotated and set on integral support "shelves"

TOGGLE CASSETTE CLIPS

Specially designed clips lock units into place and help with system stability



Clean, unobtrusive lines at junctions of the cassette unit and back member

Additional information including CAD details, CSI specs, test reports and installation instructions are found on the Product Guide by clicking this link or visiting www.ykkap.com/commercial/productguide

©2024 YKK AP America Inc. 04-5024-06