


Compatible with most YKK AP storefronts

and curtain wall systems



Anchoring Options



Concealed Anchor

- Conceals fasteners offering a finished aesthetic
- Two concealing cover options
- Pour & Debridged Thermally broken system



Exposed Anchor

- Exposed fasteners offering an industrial aesthetic
- Pressure plate integrated with anchor
- Thermally broken with Nylon Thermal Insulator

THERMASHADE® SPECS Storefront Compatibility Curtain Wall Compatibility YES 45 FI, YES 45 TU, YES 45 XT, YHS 50 FI, YHS 50 TU YCW 750 OG, YHC 300 OG, YCW 750 XT, YCW 750 SSG

Other wall systems may be customized to be compatible with ThermaShade*. Please contact your sales rep or our engineering center for more information.

Table	D = =	C+
lest	Hesults	Standards
1001	Hosuis	Otanuanus

Testing specifications will vary depending on the base curtain wall or storefront system that is used. Please refer to the specific system CSI specifications or the test reports on our product guide at www.ykkap.com.

Finish Options		
Туре	Standard	
Factory Anodized	AAMA 612	
Organic Paints	AAMA 2604 AAMA 2605	


Vertical Sunshade




A customized vertical option for our ThermaShade® is available with select systems and configurations. Please contact your local sales representative or our engineering center for more information.


Styles and Options


AVAILABLE OUTRIGGERS
















AVAILABLE LOUVERS



AVAILABLE FASCIA



Additional information including CAD details, CSI specs, test reports and installation instructions are found on the Product Guide by clicking this link or visiting www.ykkap.com/commercial/productguide

©2024 YKK AP America Inc. 09-5000-08