

# STYLEVIEW<sup>®</sup>

Windows and Doors for New Construction



2017 Edition

**YKK**  
**ap**<sup>®</sup> Quality  
inspires<sup>®</sup>




# STYLEVIEW®

Windows and Doors for New Construction



YKK AP StyleView® brand vinyl windows and sliding doors for new construction are designed for years of trouble-free use. By incorporating high performance glazing and corrosion-resistant hardware with an architecturally correct design, YKK AP offers windows and doors that deliver more value and homeowner comfort.

The YKK AP philosophy of continual investment in research and development, in testing, and in production facilities has kept us in the forefront of the industries we serve. YKK AP is a worldwide leader in architectural products, committed to producing the highest quality residential product available.







# CONTENTS

|                           |         |
|---------------------------|---------|
| Single-Hung Windows       | 3 – 4   |
| Double-Hung Windows       | 5 – 6   |
| Picture & Transom Windows | 7 – 8   |
| Casement & Awning Windows | 9 – 12  |
| Slider Windows            | 13 – 14 |
| Geometric Windows         | 15 – 16 |
| Sliding Doors             | 17      |
| Options & Accessories     | 18      |





# SINGLE-HUNG WINDOWS

Removable Upper Sash.

StyleView® single-hung windows are engineered to meet the demand for quality and craftsmanship while providing easy installation and enduring value. The removable upper sash gives StyleView single-hung windows a look comparable to traditional double-hungs. The windows provide a simple, safe opening for drywall pass-through and repair. Twin and triple continuous head and sill units can be provided, eliminating the need for mulling separate units together.

**A Integral 180 Brick Mould and J-Channel:**

Produces a rich detailed appearance while reducing labor and material costs associated with J-channel applications

**B Removable Upper Sash:**

Renders a real double-hung look while providing for simple economical repair and drywall pass-through

**C Interlocking Sash:**


Improves structural performance and adds security

**D Tilt-In Bottom Sash:**

Makes cleaning easier

**E Fusion-Welded Sloped Sill & Projected Sill Nose:**

For an architecturally correct look and improved water rating



**F Integral 1" Nail Fin:**

Provides easy user-friendly installation

**G Double Weather Stripping:**

Optimum protection against air, water, noise, and dust infiltration

**H Constant-Force Teflon®-Coated Stainless Steel Balance:**

Corrosion-resistant and never needs adjustment

**I Proprietary Cam Lock:**

Provides tight weather seal and distinctive styling with concealed fasteners

**J 3/4" Insulated Glass:**

Low-E and low-conductance spacers are standard for optimal thermal efficiency

**K Integral Lift Rail:**

Enables easy sash operation



| 1   |         | 20"     | 24"     | 28"     | 30"     | 32"     | 36"     | 38"     | 40"     | 44"     | 48"     |
|-----|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
|     | 2       | 19-1/2" | 23-1/2" | 27-1/2" | 29-1/2" | 31-1/2" | 35-1/2" | 37-1/2" | 39-1/2" | 43-1/2" | 47-1/2" |
| 36" | 35-1/2" |         |         |         |         |         |         |         |         |         |         |
| 38" | 37-1/2" |         |         |         |         |         |         |         |         |         |         |
| 44" | 43-1/2" |         |         |         |         |         |         |         |         |         |         |
| 46" | 45-1/2" |         |         |         |         |         |         |         |         |         |         |
| 48" | 47-1/2" |         |         |         |         |         |         |         |         |         |         |
| 50" | 49-1/2" |         |         |         |         |         |         |         |         |         |         |
| 52" | 51-1/2" |         |         |         |         |         |         |         |         |         |         |
| 54" | 53-1/2" |         |         |         |         |         |         |         |         |         |         |
| 60" | 59-1/2" |         |         |         |         |         |         |         |         |         |         |
| 62" | 61-1/2" |         |         |         |         |         |         |         |         |         |         |
| 66" | 65-1/2" |         |         |         |         |         |         |         |         |         |         |
| 72" | 71-1/2" |         |         |         |         |         |         |         |         |         |         |
| 74" | 73-1/2" |         |         |         |         |         |         |         |         |         |         |



### Single-Hung Windows

- ① Rough Opening
- ② Actual Window Size (frame, excluding brick mould)
- All dimensions are inches.
- Shading indicates window meets 5.7 sq. ft. egress.
- Darker shading indicates sizes with tempered glass do not meet egress. These sizes will meet egress with annealed glass.
- For twins, double rough opening of single.
- For triples, triple rough opening of single.

Also available in 80" and 84" heights. Consult ViewBuilder for specifications.



# DOUBLE-HUNG WINDOWS



YKK AP builds StyleView® double-hung windows for years of reliable, trouble-free performance. Quality construction begins with our proprietary vinyl extrusion, especially formulated for superior strength and all-weather performance. Both sashes tilt in for easy cleaning, convenient for the exterior glass of upper floors. Twin and triple continuous head and sill units can be provided, eliminating the need for mulling separate units together.

**A Integral 180 Brick Mould and J-Channel:**  
Produces a rich detailed appearance while reducing labor and material costs typical of J-channel applications


**B 3/4" Insulated Glass:**  
Low-E and low-conductance spacers are standard for optimal thermal efficiency

**C Tilt-In Bottom and Top Sash:**  
Makes cleaning easier

**D Interlocking Sash:**  
Improves structural performance and window seal

**E Double Weather Stripping:**  
Optimum protection against air, water, noise, and dust infiltration

**F Fusion-Welded Sloped Sill and Projected Sill Nose:**  
For an architecturally correct look and improved water rating



*Double-Hung window not available in Tuscan Bronze at this time*

**G Integral 1" Nail Fin:**  
Provides easy installation

**H Constant-Force Teflon®-Coated Stainless Steel Balance:**  
Corrosion-resistant and never needs adjustment

**I Proprietary Cam Lock:**  
Provides tight weather seal and distinctive styling with concealed fasteners

**J Flush-Mounted Tilt Latches:**  
Aesthetically designed to meet structural loads

**K Corrosion-Resistant Hardware:**  
For lasting durability in the harshest environments

**L Integral Lift Rail:**  
Enables easy sash operation

**M Fusion-Welded Frame and Sash:**  
Enhances structural integrity and improves energy efficiency





| ①   |         | 20"     | 24"     | 28"     | 30"     | 32"     | 36"     | 38"     | 40"     | 44"     | 48"     |
|-----|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
|     | ②       | 19-1/2" | 23-1/2" | 27-1/2" | 29-1/2" | 31-1/2" | 35-1/2" | 37-1/2" | 39-1/2" | 43-1/2" | 47-1/2" |
| 36" | 35-1/2" |         |         |         |         |         |         |         |         |         |         |
| 38" | 37-1/2" |         |         |         |         |         |         |         |         |         |         |
| 44" | 43-1/2" |         |         |         |         |         |         |         |         |         |         |
| 46" | 45-1/2" |         |         |         |         |         |         |         |         |         |         |
| 48" | 47-1/2" |         |         |         |         |         |         |         |         |         |         |
| 50" | 49-1/2" |         |         |         |         |         |         |         |         |         |         |
| 52" | 51-1/2" |         |         |         |         |         |         |         |         |         |         |
| 54" | 53-1/2" |         |         |         |         |         |         |         |         |         |         |
| 60" | 59-1/2" |         |         |         |         |         |         |         |         |         |         |
| 62" | 61-1/2" |         |         |         |         |         |         |         |         |         |         |
| 66" | 65-1/2" |         |         |         |         |         |         |         |         |         |         |
| 72" | 71-1/2" |         |         |         |         |         |         |         |         |         |         |

### Double-Hung Windows

- ① Rough Opening
- ② Actual Window Size (frame, excluding brick mould)
- All dimensions are inches.
- Shading indicates window meets 5.7 sq. ft. egress.
- Darker shading indicates sizes with tempered glass do not meet egress. These sizes will meet egress with annealed glass.
- For twins, double rough opening of single.
- For triples, triple rough opening of single.

Also available in 74" height. Consult ViewBuilder for specifications.



# TRANSOM & PICTURE WINDOWS



The high thermal efficiency of StyleView® window and door products enables enjoyment of large, stylish combinations of picture and transom windows. As a result, homeowners can open a room to more natural lighting and scenery without squandering energy.

| 1   |         | 20"     | 24"     | 28"     | 30"     | 32"     | 36"     | 38"     | 40"     | 44"     |
|-----|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
|     | 2       | 19-1/2" | 23-1/2" | 27-1/2" | 29-1/2" | 31-1/2" | 35-1/2" | 37-1/2" | 39-1/2" | 43-1/2" |
| 12" | 11-1/2" |         |         |         |         |         |         |         |         |         |
| 18" | 17-1/2" |         |         |         |         |         |         |         |         |         |
| 24" | 23-1/2" |         |         |         |         |         |         |         |         |         |
| 28" | 27-1/2" |         |         |         |         |         |         |         |         |         |

## Transom Windows

① Rough Opening ② Actual Window Size

- All dimensions are inches.
- For twins, double rough opening of single.
- For triples, triple rough opening of single.
- Units are available with factory mulling.







| 1   |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
|-----|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
|     | 12"     | 18"     | 20"     | 24"     | 30"     | 32"     | 36"     | 38"     | 40"     | 44"     | 48"     | 54"     | 60"     | 72"     | 80"     |
| 2   | 11-1/2" | 17-1/2" | 19-1/2" | 23-1/2" | 29-1/2" | 31-1/2" | 35-1/2" | 37-1/2" | 39-1/2" | 43-1/2" | 47-1/2" | 53-1/2" | 59-1/2" | 71-1/2" | 79-1/2" |
| 36" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 38" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 44" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 46" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 48" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 50" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 52" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 54" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 60" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 62" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 66" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 72" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |
| 74" |         |         |         |         |         |         |         |         |         |         |         |         |         |         |         |

## Picture Windows

- 1 Rough Opening
- 2 Actual Window Size (frame, excluding brick mould)
  - For twins, double rough opening of single.
  - For triples, triple rough opening of single.
  - All dimensions are inches.

Also available in widths up to 96" and 80", 84" and 96" heights. Maximum sizes (in inches): 96x72, 72x96, and 80x80. Consult ViewBuilder for specifications.

# CASEMENT & AWNING WINDOWS



StyleView® casement and awning windows are easily combined in multiple units to create dramatic window effects and improved ventilation in contemporary or traditional homes.

- A Integral 1 1/4" Nail Fin:**  
Provides easy installation
- B Multi-Chamber Weather Stripping:**  
Optimum protection against air, water, noise, and dust infiltration
- C 3/4" Insulated Glass:**  
Low-E and low-conductance spacers are standard for optimal thermal efficiency
- D Hinges:**  
Pivot to 90 degrees enabling cleaning exterior glass from inside the home
- E Screen Track:**  
Enables easy removal from inside the home



- F Fusion-Welded Frame and Sash:**  
Enhances structural integrity and improves energy efficiency
- G Multi-Point Lock:**  
Single handle engages multiple lock points to provide air- and water-tight seal by compressing sash securely to the frame
- H Powder-Coated Hardware (or Optional Stainless Steel):**  
Provides protection from corrosion
- I Folding Operator Handle:**  
Provides a clean look and avoids interference with window decorating treatments



# CASEMENT WINDOWS

SV

| ①   | 18"     | 20"     | 24"     | 28"     | 30"     | 36"     | 40"     |
|-----|---------|---------|---------|---------|---------|---------|---------|
| ②   | 17-1/2" | 19-1/2" | 23-1/2" | 27-1/2" | 29-1/2" | 35-1/2" | 39-1/2" |
| 24" | 23-1/2" |         |         |         |         |         |         |
| 36" | 35-1/2" |         |         |         |         |         |         |
| 42" | 41-1/2" |         |         |         |         |         |         |
| 48" | 47-1/2" |         |         |         |         |         |         |
| 52" | 51-1/2" |         |         |         |         |         |         |
| 60" | 59-1/2" |         |         |         |         |         |         |
| 66" | 65-1/2" |         |         |         |         |         |         |
| 72" | 71-1/2" |         |         |         |         |         |         |
| 76" | 75-1/2" |         |         |         |         |         |         |
| 80" | 79-1/2" |         |         |         |         |         |         |


## Casement Windows

### ① Rough Opening


### ② Actual Window Size

- All dimensions are inches.
- Light shading indicates window meets 5.7 sq. ft. egress with standard hinges.
- Darker shading indicates egress compliance if egress hinges are specified. A casement with standard hinges cannot be converted to egress compliance.
- For twins, double rough opening of single.
- For triples, triple rough opening of single.

Left Hinge



Right Hinge



### Casement Vent Layout:

When ordering, specify left or right hinge configuration as viewed from outside.



# CASEMENT PICTURE WINDOWS



| 1   | 20" 24" 28" 30" 36" 48" 60" |         |         |         |         |         |         |
|-----|-----------------------------|---------|---------|---------|---------|---------|---------|
|     | 19-1/2"                     | 23-1/2" | 27-1/2" | 29-1/2" | 35-1/2" | 47-1/2" | 59-1/2" |
| 36" | 35-1/2"                     |         |         |         |         |         |         |
| 42" | 41-1/2"                     |         |         |         |         |         |         |
| 48" | 47-1/2"                     |         |         |         |         |         |         |
| 52" | 51-1/2"                     |         |         |         |         |         |         |
| 60" | 59-1/2"                     |         |         |         |         |         |         |
| 66" | 65-1/2"                     |         |         |         |         |         |         |
| 72" | 71-1/2"                     |         |         |         |         |         |         |
| 80" | 79-1/2"                     |         |         |         |         |         |         |

## Casement Picture Windows

1 Rough Opening 2 Actual Window Size































- All dimensions are inches.
- For twins, double rough opening of single.
- For triples, triple rough opening of single.





# AWNING WINDOWS

SV

| 1   |         | 24"                                                                               | 36"                                                                               | 40"                                                                               | 48"                                                                               | 56"                                                                               | 60"                                                                                |
|-----|---------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
|     | 2       | 23-1/2"                                                                           | 35-1/2"                                                                           | 39-1/2"                                                                           | 47-1/2"                                                                           | 55-1/2"                                                                           | 59-1/2"                                                                            |
| 18" | 17-1/2" |  |  |  |  |  |  |
| 20" | 19-1/2" |  |  |  |  |  |  |
| 24" | 23-1/2" |  |  |  |  |  |  |
| 28" | 27-1/2" |  |  |  |  |  |  |
| 36" | 35-1/2" |  |  |  |  |  |  |

## Awning Windows

① Rough Opening

② Actual Window Size

- All dimensions are inches.
- Width for twins, double rough opening of single.
- Width for triples, triple rough opening of single.
- Height for multiples: multiply single rough opening by number you choose to stack.




# SLIDER WINDOWS



StyleView® slider windows extend the opportunity for creative window solutions. The functionality and warm look of these windows make them appropriate for contemporary or traditional homes.

- A Double Weather Stripping:** Optimum protection against air, water, noise, and dust infiltration
- B 3/4" Insulated Glass:** Low-E and low-conductance spacers for optimal thermal efficiency and to minimize risk of condensation
- C Proprietary Cam Lock:** Provides tight weather seal and distinctive styling with concealed fasteners
- D Brass Rollers:** For smooth, trouble-free operation
- E Removable Sash:** Enables easier cleaning from inside the home







| 1   |         | 24"     | 36"     | 48"     | 50"     | 54"     | 60"     | 64"     | 72"     |
|-----|---------|---------|---------|---------|---------|---------|---------|---------|---------|
|     | 2       | 23-1/2" | 35-1/2" | 47-1/2" | 49-1/2" | 53-1/2" | 59-1/2" | 63-1/2" | 71-1/2" |
| 24" | 23-1/2" |         |         |         |         |         |         |         |         |
| 36" | 35-1/2" |         |         |         |         |         |         |         |         |
| 42" | 41-1/2" |         |         |         |         |         |         |         |         |
| 44" | 43-1/2" |         |         |         |         |         |         |         |         |
| 48" | 47-1/2" |         |         |         |         |         |         |         |         |
| 50" | 49-1/2" |         |         |         |         |         |         |         |         |
| 54" | 53-1/2" |         |         |         |         |         |         |         |         |
| 60" | 59-1/2" |         |         |         |         |         |         |         |         |

**Slider Windows**


- ① Rough Opening
- ② Actual Window Size (frame, excluding brick mould)
- All dimensions are inches.
- Shading indicates window meets 5.7 sq. ft. egress.

# GEOMETRIC WINDOWS




StyleView® geometric windows, available in a wide variety of standard and custom shapes, offer exciting opportunities to expand the value of windows as an architectural asset.

## Circle



| Size Code | Actual Window Size |
|-----------|--------------------|
| SVCR2424  | 23-1/2" x 23-1/2"  |
| SVCR3030  | 29-1/2" x 29-1/2"  |
| SVCR3636  | 35-1/2" x 35-1/2"  |
| SVCR4848  | 47-1/2" x 47-1/2"  |

## Half Round




| Size Code | Actual Window Size | Size Code | Actual Window Size |
|-----------|--------------------|-----------|--------------------|
| SVHR2412  | 23-1/2" x 11-1/2"  | SVHR4422  | 43-1/2" x 21-1/2"  |
| SVHR2814  | 27-1/2" x 13-1/2"  | SVHR4824  | 47-1/2" x 23-1/2"  |
| SVHR3015  | 29-1/2" x 14-1/2"  | SVHR5427  | 53-1/2" x 26-1/2"  |
| SVHR3216  | 31-1/2" x 15-1/2"  | SVHR5628  | 55-1/2" x 28-1/2"  |
| SVHR3618  | 35-1/2" x 17-1/2"  | SVHR6030  | 59-1/2" x 29-1/2"  |
| SVHR3819  | 37-1/2" x 18-1/2"  | SVHR6432  | 63-1/2" x 31-1/2"  |
| SVHR4020  | 39-1/2" x 19-1/2"  | SVHR7236  | 71-1/2" x 35-1/2"  |

## Oval & Half Oval



| Size Code | Actual Window Size | Size Code | Actual Window Size |
|-----------|--------------------|-----------|--------------------|
| SVOV2436  | 23-1/2" x 35-1/2"  | SVHO1824  | 17-1/2" x 23-1/2"  |
| SVOV3656  | 35-1/2" x 55-1/2"  | SVHO2836  | 27-1/2" x 35-1/2"  |

## Elliptical




| Size Code | Actual Window Size |
|-----------|--------------------|
| SVEP6018  | 59-1/2" x 17-1/2"  |
| SVEP7220  | 71-1/2" x 19-1/2"  |

## Gothic



| Size Code | Actual Window Size | Size Code | Actual Window Size |
|-----------|--------------------|-----------|--------------------|
| SVGO1836  | 17-1/2" x 35-1/2"  | SVGO2856  | 27-1/2" x 55-1/2"  |
| SVGO2040  | 19-1/2" x 39-1/2"  | SVGO3060  | 29-1/2" x 59-1/2"  |
| SVGO2244  | 21-1/2" x 43-1/2"  | SVGO3672  | 35-1/2" x 71-1/2"  |
| SVGO2448  | 23-1/2" x 47-1/2"  |           |                    |

## Half Gothic




| Size Code (left) | Size Code (right) | Actual Window Size |
|------------------|-------------------|--------------------|
| SVHGL1854        | SVHGR1854         | 17-1/2" x 53-1/2"  |
| SVHGL2260        | SVHGR2260         | 21-1/2" x 59-1/2"  |
| SVHGL2666        | SVHGR2666         | 25-1/2" x 65-1/2"  |
| SVHGL2872        | SVHGR2872         | 27-1/2" x 71-1/2"  |

## Octagon



| Size Code | Actual Window Size |
|-----------|--------------------|
| SVOC2424  | 23-1/2" x 23-1/2"  |
| SVOC3232  | 31-1/2" x 31-1/2"  |
| SVOC3636  | 35-1/2" x 35-1/2"  |
| SVOC4848  | 47-1/2" x 47-1/2"  |

## Quarter Round



| Size Code (left) | Size Code (right) | Actual Window Size |
|------------------|-------------------|--------------------|
| SVQRL20          | SVQRR20           | 19-1/2" x 19-1/2"  |
| SVQRL24          | SVQRR24           | 23-1/2" x 23-1/2"  |
| SVQRL28          | SVQRR28           | 27-1/2" x 27-1/2"  |
| SVQRL30          | SVQRR30           | 29-1/2" x 29-1/2"  |
| SVQRL32          | SVQRR32           | 31-1/2" x 31-1/2"  |
| SVQRL36          | SVQRR36           | 35-1/2" x 35-1/2"  |
| SVQRL48          | SVQRR48           | 47-1/2" x 47-1/2"  |

## Geometric Windows

- All dimensions in inches
- Custom shapes available



16



# SLIDING DOORS

StyleView® sliding doors are a beautiful option for giving a room an appealing focal point. They invite natural light into the room and take advantage of its views. Like all StyleView window and door products, our sliding doors are meticulously crafted with the finest materials and workmanship. StyleView sliding doors are designed for powerful visual appeal and years of security, energy-saving comfort and trouble-free operation.



*Not available in Tuscan Bronze or Stone colors at this time.*

- A Full Perimeter Weatherstripping:** Protection against air, water, noise, and dust infiltration
- B Heavy-Duty Lock:** Provides security and tight weather seal
- C Upgraded Hardware:** Precision-fit and corrosion-resistant for long lasting performance
- D Heavy-Duty Extruded Sliding Screen Door:** Standard with all StyleView doors
- E Wide Track Adjustable Rollers:** Encased bearings for smooth operation
- F Aluminum Threshold:** Lasting durability

|         |         |         |         |         |            |
|---------|---------|---------|---------|---------|------------|
|         |         | 60"     | 72"     | 96"     |            |
|         |         | 59-1/4" | 71-1/4" | 95-1/4" |            |
| 80"     | 79-1/2" |         |         |         | Patio Door |
|         |         | 30"     | 36"     | 48"     |            |
|         |         | 29-3/8" | 35-3/8" | 47-3/8" |            |
| 80"     | 79-1/2" |         |         |         | Sidelite   |
|         |         | 60"     | 72"     | 96"     |            |
|         |         | 59-1/4" | 71-1/4" | 95-1/4" |            |
| 12-1/2" | 12"     |         |         |         | Transom    |

## Sliding Doors

① Rough Opening ② Actual Door/ Window Size

- All dimensions are inches.
- Combination width, one sidelite: add rough opening for door to rough opening for sidelite.
- Combination width, two sidelites: add rough opening for door to 2x rough opening for sidelite + 1/4".
- Combination height: add rough opening of door to rough opening of transom + 1/4".





# WINDOW AND DOOR OPTIONS

## COLORS



*\*not available for standard sliding door at this time*  
*\*\*not available for double-hung, sliding windows, or standard sliding doors at this time*  
 Color swatches are representative only.

## ENERGY EFFICIENCY GLASS




270 Low-E (Standard)  
 Reduces heat gain 50% and  
 blocks 86% of sun's UV rays




366 Low-E  
 Reduces heat gain 64% and  
 blocks 95% of sun's UV rays

## GRID PATTERNS




## INSTALLATION OPTIONS


The variety of installation options span a rich millwork look with a brick mould exterior to flush frames that accommodate stucco and block construction.



Nail Fin  
(Standard)




Nail Fin with Brick  
Mould/J-Channel Option



Flange for Block  
Construction

## GLASS APPEARANCE


Select from three glass appearance options for enhanced style, light management, and privacy:




## GRID STYLES (FACE WIDTH: 7/8")



Flat Grids  
Between Glass



Sculptured Grids  
Between Glass



Simulated Divided  
Lights




# STYLEVIEW® WINDOW AND DOOR QUALITY GUARANTEED

**YKK AP stands behind every StyleView window and door product with a Limited Lifetime Warranty.**

## ENERGY STAR WINDOWS AND DOORS PERFORMANCE CRITERIA

### Energy Star Climate Zones



### ENERGY STAR® Qualification Criteria for Residential Windows

Phase 2: Effective January, 2015

| Climate Zone  | U-Factor <sup>1</sup> | SHGC <sup>2</sup> |                               |
|---------------|-----------------------|-------------------|-------------------------------|
| Northern      | ≤ 0.27                | Any               | Prescriptive                  |
|               | = 0.28                | ≥ 0.32            | Equivalent Energy Performance |
|               | = 0.29                | ≥ 0.37            |                               |
| North-Central | ≤ 0.30                | ≤ 0.40            |                               |
| South-Central | ≤ 0.30                | ≤ 0.25            |                               |
| Southern      | ≤ 0.40                | ≤ 0.25            |                               |

| Glazing Level | U-Factor <sup>1</sup> | SHGC <sup>2</sup>          |        |
|---------------|-----------------------|----------------------------|--------|
| Opaque        | ≤ 0.17                | No Rating                  |        |
| ≤ ½-Lite      | ≤ 0.25                | ≤ 0.25                     |        |
| > ½-Lite      | ≤ 0.30                | Northern and North-Central | ≤ 0.40 |
|               |                       | South-Central and Southern | ≤ 0.25 |

<sup>1</sup> Btu/h·ft<sup>2</sup>·°F

<sup>2</sup> Fraction of incident solar radiation

ENERGY STAR Phase 2 provides no performance guidelines for impact-resistant windows and doors.

## STYLEVIEW WINDOWS AIR, STRUCTURAL, WATER PERFORMANCE

| Window Type                               | Size     | Air Infiltration @ 1.57 PSF | Water PSF | Structural PSF | Structural Class | Florida Certification Number |
|-------------------------------------------|----------|-----------------------------|-----------|----------------|------------------|------------------------------|
| Single-Hung                               | 36 x 80  | 0.11                        | 7.50      | 37.5           | DP25             | —                            |
|                                           | 48 x 72  | 0.10                        | 7.50      | 45.0           | DP25             | —                            |
|                                           | 36 x 72  | 0.10                        | 7.50      | 52.5           | DP35             | 15081                        |
|                                           | 48 x 72* | 0.10                        | 7.50      | 75.0           | DP50             | 8114                         |
| Twin Single-Hung (Continuous Head & Sill) |          |                             |           |                |                  |                              |
|                                           | 72 x 72  | 0.11                        | 5.25      | 37.5           | DP35             | 15140                        |
| Double-Hung                               | 36 x 62  | 0.12                        | 7.50      | 37.5           | DP25             | —                            |
|                                           | 48 x 72  | 0.12                        | 7.50      | 37.5           | DP25             | —                            |
|                                           | 44 x 72* | 0.12                        | 7.50      | 75.0           | DP50             | 10385                        |
| Casement                                  | 36 x 72  | 0.01                        | 7.50      | 52.5           | DP35             | 15153                        |
|                                           | 36 x 72* | 0.01                        | 7.50      | 75.0           | DP50             | 15153                        |
| XO Slider                                 | 72 x 60  | 0.05                        | 3.75      | 37.5           | DP40             | 14595                        |
| Picture                                   | 72 x 96  | 0.00                        | 7.50      | 52.5           | DP35             | 15141                        |
|                                           | 72 x 72  | 0.00                        | 7.50      | 75.0           | DP50             | 8197                         |
| OX HD Sliding Door                        | 96 x 96  | 0.12                        | 7.50      | 75.0           | DP50             | 16605                        |
| XX HD Sliding Door                        | 96 x 96  | 0.02                        | 7.50      | 75.0           | DP50             | 16605                        |
| OXO HD Sliding Door                       | 144 x 96 | 0.07                        | 6.89      | 75.0           | DP45             | 16605                        |
| OXO** HD Sliding Door                     | 144 x 96 | 0.07                        | 7.50      | 75.0           | DP50             | 16605                        |
| OXOX HD Sliding Door                      | 192 x 96 | 0.10                        | 6.89      | 75.0           | DP45             | 16605                        |
| OXOX** HD Sliding Door                    | 192 x 96 | 0.10                        | 7.50      | 75.0           | DP50             | 16605                        |

\* Reinforced

\*\* With sill dam extender

## STYLEVIEW WINDOWS AND DOORS THERMAL PERFORMANCE

To determine thermal performance ratings, enter product specifications in



4234 Ocmulgee Blvd East  
Macon, Georgia 31217  
p: 866-348-9091  
f: 478-744-6221  
[www.ykkap.com/residential](http://www.ykkap.com/residential)

ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. TEFLON is a registered trademark of E.I. du Pont de Nemours and Company.

© 2017 YKK AP America Inc.